



## SAFETY DATA SHEET

### CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Cleaning agent.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Cleenol Group Ltd  
Neville House  
Beaumont Road  
Banbury  
Oxon OX16 1RB  
UK  
Tel : +44 (0)1295 251721  
Fax : +44 (0)1295 269561  
sales@cleenol.co.uk

**Manufacturer** Cleenol Group Ltd  
Neville House  
Beaumont Road  
Banbury  
Oxon OX16 1RB  
UK  
Tel : +44 (0)1295 251721  
Fax : +44 (0)1295 269561  
sales@cleenol.co.uk

##### 1.4. Emergency telephone number

**Emergency telephone** Poisons Information Specialist  
National Poisons Information Service  
Birmingham  
B18 7QH  
Tel: 0121 507 5122

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification

**Physical hazards** Not Classified

**Health hazards** Eye Dam. 1 - H318 STOT SE 3 - H336 Asp. Tox. 1 - H304

**Environmental hazards** Aquatic Chronic 3 - H412

**Classification (67/548/EEC or 1999/45/EC)** Xn;R65. Xi;R41. R52/53,R66.

## CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

### 2.2. Label elements

#### Pictogram



#### Signal word

Danger

#### Hazard statements

H304 May be fatal if swallowed and enters airways.  
 H318 Causes serious eye damage.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P261 Avoid breathing vapour/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P331 Do NOT induce vomiting.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with national regulations.

#### Contains

WHITE SPIRIT, FATTY ALCOHOL ETHOXYLATE, PROPAN-2-OL, FATTY ALCOHOL ETHOXYLATE, SODIUM DODECYL BENZENE SULPHONATE

### 2.3. Other hazards

#### Other Hazards

None

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>WHITE SPIRIT</b>	<b>10-30%</b>
CAS number: 64742-82-1	EC number: 265-185-4
<b>Classification</b> Flam. Liq. 3 - H226 Asp. Tox. 1 - H304 STOT SE 3 - H336 STOT SE 3 - H336 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. N;R51/53. R10,R66,R67.
<b>PINE OIL</b>	<b>10-30%</b>
CAS number: —	
<b>Classification</b> Eye Irrit. 2 - H319	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xi;R36.

## CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

<b>FATTY ALCOHOL ETHOXYLATE</b>		<b>5-10%</b>
CAS number: 160901-19-9		
<b>Classification</b> Eye Dam. 1 - H318 Acute Tox. 4 - H302	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R22. Xi;R41.	
<b>PROPAN-2-OL</b>		<b>5-10%</b>
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-0000
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Xi;R36 R67	
<b>FATTY ALCOHOL ETHOXYLATE</b>		<b>1-5%</b>
CAS number: 24938-91-8		
M factor (Acute) = 1		
<b>Classification</b> Acute Tox. 4 - H302 Eye Dam. 1 - H318 Aquatic Acute 1 - H400	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R22. Xi;R41. N;R50.	
<b>SODIUM DODECYL BENZENE SULPHONATE</b>		<b>1-5%</b>
CAS number: 68411-30-3	REACH registration number: 01-2119489428-22-XXXX	
<b>Classification</b> Skin Irrit. 2 - H315 Eye Dam. 1 - H318	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xi;R38,R41.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
<b>Ingestion</b>	Do not induce vomiting. Never give anything by mouth to an unconscious person. Remove affected person from source of contamination. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.

## CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

**Eye contact** Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** May be harmful if inhaled.  
**Ingestion** May be harmful if swallowed.  
**Skin contact** May be harmful in contact with skin.  
**Eye contact** May cause eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Specific treatments** Seek medical attention if irritation or symptoms persist. Symptomatic treatment

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Use fire-extinguishing media suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Burning may produce irritating, toxic and obnoxious fumes. Oxides of Carbon, Nitrogen and Sulphur.

### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Avoid or minimise the creation of any environmental contamination.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.4. Reference to other sections

**Reference to other sections** See section 3,8 & 13 for further information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

##### WHITE SPIRIT (CAS: 64742-82-1)

##### Ingredient comments

WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

##### Protective equipment



**Appropriate engineering controls**

Not relevant.

**Eye/face protection**

The following protection should be worn: Chemical splash goggles.

**Hand protection**

Use protective gloves.

**Other skin and body protection**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**Hygiene measures**

Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**Respiratory protection**

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

**Appearance** Clear, yellowish liquid.

**Odour** Characteristic.

**pH** 6-8

**Initial boiling point and range** 100°C @ 760 mm Hg

**Relative density** 1.041 @ 20°C

#### 9.2. Other information

**Other information** None.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** No test data specifically related to reactivity available for this product or its ingredients.

#### 10.2. Chemical stability

## CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

**Stability** Stable at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None known.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid contact with the following materials: Acids. Oxidising agents.

### 10.5. Incompatible materials

**Materials to avoid** None known.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**ATE oral (mg/kg)** 4,444.44

**Inhalation** Harmful by inhalation. May cause respiratory system irritation.

**Ingestion** Harmful if swallowed.

**Skin contact** Harmful in contact with skin. Irritating to skin.

**Eye contact** Irritating to eyes.

**Target organs** Skin Eyes Respiratory system, lungs

## SECTION 12: Ecological Information

**Ecotoxicity** No negative effects on the aquatic environment are known.

### 12.1. Toxicity

**Toxicity** The product is not believed to present a hazard due to its physical nature.

### 12.2. Persistence and degradability

**Persistence and degradability** The product is biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

### 12.4. Mobility in soil

**Mobility** The product is soluble in water.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

## CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

### 13.1. Waste treatment methods

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

No transport warning sign required.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78 and the IBC Code**

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.  
Introduction to Local Exhaust Ventilation HS(G)37.  
CHIP for everyone HSG228.  
Approved Classification and Labelling Guide (Sixth edition) L131.

#### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

### SECTION 16: Other information

## CLEENOL INDUSTRIAL HEAVY DUTY DEGREASER

<b>Revision date</b>	27/01/2016
<b>Revision</b>	7
<b>Supersedes date</b>	03/11/2015
<b>SDS number</b>	C16
<b>Risk phrases in full</b>	R10 Flammable. R11 Highly flammable. R22 Harmful if swallowed. R35 Causes severe burns. R36 Irritating to eyes. R38 Irritating to skin. R41 Risk of serious damage to eyes. R50 Very toxic to aquatic organisms. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.